

AMG350-5G SERIES INDUSTRIAL UNMANAGED SWITCHES WITH OPTIONAL 30W POE



Industrial Ethernet Solutions

AMG's unmanaged Ethernet switches provide 100Mbps or Gigabit Ethernet switching for simple edge network applications with optional 30W PoE. Available with 5x Gigabit RJ45 ports.



Gigabit up to x5	Gigabit up to x4	Temp -40°C~+75°C	Mounting DIN/Surface	PSU x2 Dual	Protection IP40

[AMG350-5G Series]

/ OVERVIEW

Designed in a compact DIN rail or wall mount housing, the AMG350 series unmanaged Ethernet switches are ideally suited for connecting edge devices to Ethernet networks where more complex management functions are not required.

Available in both non-PoE models as well as PoE models for IEEE802.3at 30W they are suitable for powering PoE devices over a wide industrial operating temperature range.

Fitted with dual redundant power inputs ensures maximum operating reliability and the highest levels of performance.

A wide range of models are available in the AMG350 product range to suit all unmanaged switch design requirements.

PSUs need to be ordered separately.

/ FEATURES

- Compact size – ideal for confined spaces, including camera poles and roadside cabinets
- Innovative thermally efficient housing ensures high levels of device reliability under full load
- -40°C to +75°C temperature maintains performance in extreme conditions
- Plug & Play – no need for any user configuration
- DIN rail mountable – quick to install and remove for maintenance
- Dual redundant power inputs
- Supports optional 15W and 30W PoE
- Auto-Negotiation (802.3u) – automatically determines the best connection speed
- Supports wide ranging DC or AC power inputs
- Manufactured in the United Kingdom
- AMG Lifetime Support Warranty

Specifications.

Standards.

IEEE802.3i	10Base-T
IEEE802.3u	100Base-TX
IEEE802.3ab	1000Base-T
IEEE802.3af	15W PoE
IEEE802.3at	30W PoE+
IEEE802.3x	Flow Control

Jumbo Frames	9.6Kbytes
Address Table	2K MAC Entries
Switch Fabric	10 Gbps
Buffer Memory	1M bits

Interface.

LED Indicators	2x Power RJ45 Link/Activity RJ45 Speed (Non-PoE Models Only) PoE (PoE Models Only)
RJ45 Ports	5x 10/100/1000T(X) RJ45 with Auto MDI/MDI-X with 2 kV Isolation Protection
Power	1x 4-way Screw Terminal

Power.

Power Inputs	2
Operating Voltage:	
Non-PoE Models	12-56V _{DC} or 18-36V _{AC}
30W PoE Models	48-56V _{DC}
Power Consumption	3W Max (without PoE Load)
Total PoE Budget	120W Max (model dependent)
PSE Modes	Mode A
PoE Enabled Ports	Ports 1-4 (model dependent)
Protection	Reverse Polarity Overload Current

Packaging.

Shipping Weight	0.52kg / 1.15lb
Dimensions	(W x D x H) 175 x 160 x 50 mm 6.83 x 6.30 x 1.97 in

Mechanical.

Housing	Anodised Aluminium
Dimensions:	(W x D x H) 37 x 88 x 107 mm 1.46 x 3.46 x 4.21 in
Excluding DIN & Wall Mounts	
IP Rating	IP40
Installation	Wall Mount or DIN-Rail
Weight	0.3kg / 0.66lb

Environmental.

Operating Temp.	-40°C to +75°C
Storage Temp.	-40°C to +85°C
Humidity	5% to 95% (non-condensing)
MTBF	>500,000 hours
MTBF Standard	MIL-HDBK-217F GF 25°C
Heat Dissipation	10 BTU/h (Non-PoE) 420 BTU/h (30W PoE)
Cooling	Passive Cooling
Noise Level	0 dBA

Regulatory.

Safety	IEC/EN 62368-1
EMI	EN 55032 Class A CISPR 32 EN55024 FCC Part 15B Class A
EMS	EN 61000-4-2 (ESD) EN 61000-4-4 (EFT) EN 61000-4-5 (Surge)
Shock	IEC 60068-2-27
Free Fall	IEC 60068-2-32
Vibration	IEC 60068-2-6
Environmental	Reach RoHS WEEE

Designed to meet NEMA TS2 & EN 50121-4


Part Numbers.

5 Port Unmanaged 1Gb Ethernet Switches

AMG350-5G	5x 10/100/1000TX
AMG350-4GAT-1G-P120	4x 10/100/1000TX 30W PoE (120W Max), 1x 10/100/1000TX

Included Accessories.

DIN Rail Adapter Rear Mounted Metal DIN Rail Clip & Screws For DIN Rail Mounting AMG350 Series Products
Wall Mounting Brackets 2x Wall Mounting Brackets & Screws For Wall / Surface Mounting AMG350 Series Products



Recommended PSUs.

Non-PoE Models


AMGPSU-I12-P24 DIN-Rail Mount Industrial Grade PSU, -40 to +70°C, 12VDC, 24W

PoE Models

AMGPSU-I48L-P120 DIN-Rail Mounting Light Industrial Grade PSU, -20 to +60°C, 48-55VDC, 120W

AMGPSU-I48-P120 DIN-Rail Mounting Industrial Grade PSU, -40 to +70°C, 47-53VDC, 120W

AMGPSU-I48-P240 DIN-Rail Mounting Industrial Grade PSU, -40 to +70°C, 48-53VDC, 240W

Proud to be a British
Manufacturer 

In a continuing effort to improve and advance technology, product specifications are subject to change without notice. Please visit www.amgsystems.com for the latest product specifications.