

DS-D42C04-N LED Display Controller

DS-D42C04-N LED Display Controller, used with LED outdoor full-color display screens, can achieve seamless stitching of the video wall in any dimensions. It is applicable to stadiums, airports, stations, banks, advertisements, family cinemas, etc.



- 4 Gigabit Ethernet output ports, with up to 1920 × 1200@60 Hz signal input
- HDMI input interface: 1920 × 1200@60 Hz
- DVI input interface: Up to 1920 × 1200@60 Hz
- Competent with load capacity: 2.3 MP
- 3840 Hz high refresh rate and nanosecond response time ensure smooth video pictures.





Specification

Model		DS-D42C04-N		
Interface	Video & Audio Input	1 × DVI, 1 x HDMI, 1 x Audio		
	Video & Audio Output	4*RJ45		
	Network Interface	4		
	Control Interface	USB × 1		
Processing Performance	Max. Load Capacity	2048 x 1152@60Hz or 1920 x 1200@60Hz		
	Frame Frequency	50/60 Hz		
	Refresh Rate	3840 Hz		
	Processing Depth	8 bit		
	Grey Level	16 bit		
	Display Color	281 trillion		
	Brightness Control	Automatic/manual		
	Max. Resolution of Bar Display	NO		
Power	Max. Consumption	16 W		
	Average Consumption	16 W		
	Input Voltage	AC100~240V@50/60HZ		
Working Environment	Working Temperature	-10 °C to 45 °C (14 °F to 113 °F)		
	Working Humidity	10% to 90%		
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)		
	Storage Humidity	10% to 90%		
General	Product Dimensions (W \times H \times D)	428 mm × 250 mm × 44.4 mm (16.85" × 9.84" × 1.75")		
	Package Dimensions (W × H × D)	550 mm × 440 mm × 175 mm (21.65" × 17.32" × 6.89")		
	Net Weight	2.9 kg (6.39 lb)		
	Gross Weight	5.5 kg (10.10 lb)		
	Packing List	1 × power cord、1 × USB cable、1 × DVI cable		

^{*}DS-D4204-N SPEC



Available Model

DS-D42C04-N

Physical Interface



Interface	Description	Interface	Description	
-----------	-------------	-----------	-------------	--



Accessory

Optional

DS-D44A0FO-D Outdoor Fixed LED Displays	DS-D4280FO Outdoor Fixed LED Displays	DS-D42A6FO-D Outdoor Fixed LED Displays	DS-D4480FO P8 Fixed Outdoor LED Display Unit	DS-D4240FO Outdoor Fixed LED Displays
DS-D4250FO Outdoor Fixed LED Displays	DS-D44A6FO-D Outdoor Fixed LED Displays	DS-D4260FO Outdoor Fixed LED Displays	DS-D4450FO P5 Fixed Outdoor LED Display Unit	DS-D44A0FO P10 Fixed Outdoor LED Display Unit
)-()-(
DS-D4440FO P4 Fixed Outdoor LED Display Unit	DS-D4460FO P6 Fixed Outdoor LED Display Unit	DS-D42A0FO Outdoor Fixed LED Displays	DS-D4426RI-CAF P2.6 indoor rental LED display	
			Total Carry	

HIKVISION'

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T +91-22-28469900 sales@pramahikvision,com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thalland T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T+31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 [216]521 7070- 7074 sales,tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33[0]1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan † +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T+7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-(0)31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com