

## DS-K5671-3XF/ZU Face Recognition Terminal



DS-K5671-3XF/ZU face recognition terminal is a kind of access control device integrated with temperature screening function. It can be installed on and work with turnstile, which can fast take skin-surface temperature and upload abnormal temperature event to the center, so that it can be widely applied in multiple scenarios, such as enterprises, stations, dwellings, factories, schools, campus and so on.

- Compatible with Hikvision turnstile
- Communicates with the third-party turnstile via IO output or Wiegand
- Temperature measuring range: 30 °C to 45 °C (86 °F to 113 °F), accuracy: 0.1 ° C, deviation: ± 0.5 °C
- Recognition distance: 0.3 to 2 m
- Face mask detection
- Displays temperature measurement results on the authentication page
- 50,000 face capacity and 100,000 event capacity
- Face recognition duration < 0.2 s/User
- face recognition accuracy rate ≥ 99%

**\*COMPLIANCE NOTICE:** The thermal series products might be subject to export controls in various countries or regions, including without limitation, the United States, European Union, United Kingdom and/or other member countries of the Wassenaar Arrangement. Please consult your professional legal or compliance expert or local government authorities for any necessary export license requirements if you intend to transfer, export, re-export the thermal series products between different countries.



## ▪ Specification


Model		DS-K5671-3XF/ZU
<b>System</b>	Operation system	Linux
<b>Temperature measurement</b>	Temperature range	30 °C to 45 °C (86 °F to 113 °F)
	Sensor	Vanadium Oxide uncooled sensor
	Resolution	120 × 160
	Frame rate	25 fps
	FoV	37.2° × 50°
	Measurement accuracy	0.1 °C
	Measurement deviation	± 0.5 °C, without black body calibration
	Measuring distance	0.3 to 2 m
<b>Display</b>	Size	7-inch
	Resolution	1024 × 600
	Type	Touch screen
<b>Video</b>	Pixel	2 MP
	Lens	Dual-lens
	WDR	Support
	Video standard	PAL (Default)/NTSC
<b>Network</b>	Wired network	Support, 10/100/1000 Mbps self-adaptive
	Wi-Fi	Support
	3G/4G	Not support
	Bluetooth	Not support
<b>Interface</b>	Network interface	1
	RS-485	1
	Wiegand	1
	Lock output	1
	Exit button	1
	Door contact input	1
	IO input	2
	IO output	1
	TAMPER	1
	USB	2
<b>Capacity</b>	Face capacity	50,000
	Event capacity	100,000

<b>Authentication</b>	Face recognition duration	< 0.2 s per person
	Face recognition distance	0.3 to 2 m
	Multiple faces detection	Not support
	Face anti-spoofing	Support
	Live view	Support
	Audio prompt	Support
<b>General</b>	Indicator	Support
	Power supply	12 VDC/2 A
	Working temperature	0 °C to 50 °C (32 °F to 122 °F) For temperature measurement: 10 °C to 35 °C (50 °F to 95 °F)
	Working humidity	10 to 90% (No condensing)
	Application environment	Indoor and windless environment use only

### ▪ Available Model

DS-K5671-3XF/ZU

### ▪ Dimension



Distributed by

**HIKVISION****Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 [216]521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com