


## DS-D4218FI-CWF/III Full-Color LED Display

DS-D4218FI-CWF is the new generation small pixel pitch indoor full-color LED display. LED video wall features in seamlessness, high brightness/contrast, wide viewing angle, and accurate color restoration, achieving good visual effect. It is widely used in places such as monitoring center, command center, conference room, report hall, and exhibition hall.




- Seamlessly splice images in rows and columns.
- Easily form standard 1920 × 1080 and 3840 × 2160 screens, achieving high definition dot-by-dot display.
- Automatically adapt signal sources to screens without the help of a video processing equipment.
- Easily optimize images with low resolution by improving definition, contrast and saturation with Pix Master technology.
- Dynamically enhance image parameters such as contrast, sharpness, saturation, color temperature and gamut to get the image more vivid.
- A signal input of 4K resolution at 30 Hz, and an output of up to 4K resolution for a single device.
- Use the buttons on the panel of sending card to adjust brightness and switch signal.
- Use the Hikvision remote control (optional) to navigate through menu after access to the multi-functional card.
- Automatically remove moisture to protect lamp boards from water damage when the device is kept in a humid environment or left unused for a long time.
- Back up signals and power supplies (optional) to maintain a reliable system.
- Real-time cabinet temperature and voltage checking to guarantee product safety.
- Use the sending card to input HDMI, DVI, and DP signals.
- Network interface output.
- Remote configuration via the debugging network interface.
- Easy to disassemble lamp board, power supply, and receiving card on the front side with modular unit structure.
- Precise fool-proof design of lamp boards with magnetic adsorption to prevent wrong installation.
- Three-axis XYZ structure designed to perfectly adjust the flatness of the entire screen.
- Rapidly eliminate bright and dim lines with no need of professional equipment or operations.




## ▪ Specification

Model		DS-D4218FI-CWF/III
<b>Cabinet</b>	Pixel Configuration	SMD Triad LED
	Pixel Pitch Category	P1.8
	Pixel Pitch	1.875 mm
	Modules Component	2 × 4
	Dimensions (W × H × D)	600 mm × 337.5 mm × 50.9 mm (23.62" × 13.29" × 2.00")
	Resolution	320 × 180
	Area	0.2025 m <sup>2</sup>
	Weight	5.4 Kg (11.9 lb)
	Pixel Density	284444 dots/m <sup>2</sup>
	Lamp Board Housing	No housing
	Cabinet Material	Magnalium
	Maintenance Method	Front maintenance for all components
	Cabinet Flatness	0.1 mm
	Protection Level	Front protection level IP60
<b>Display</b>	White Balance Brightness	800 cd/m <sup>2</sup>
	Color Temperature	3000 K to 10000 K adjustable
	Viewing Angle	Horizontal 160°, vertical 160°
	Contrast Ratio	≥ 5000:1
	Color Uniformity	≤ ± 0.003Cx, Cy
	Brightness Uniformity	≥ 97%
<b>Processing Performance</b>	Driving Method	Constant current driving
	Frame Frequency	60 Hz
	Refresh Rate	Up to 3840 Hz
	Grey Level	Up to 16 bit
	Display Color	281 trillion
<b>Power</b>	Power Supply	110~220 VAC ± 15%
	Max. Consumption	≤ 345 W/m <sup>2</sup>
	Average Consumption	< 115 W/m <sup>2</sup>
<b>Working Environment</b>	Working Temperature	-10-40 °C
	Working Humidity	10%~80% RH
	Storage Humidity	10%~80% RH
	Storage Temperature	-20~60 °C
<b>General</b>	Gross Weight	9.6 Kg (21.2 lb)
	Package Dimension (W × H × D)	796 mm × 484 mm × 192 mm (31.33" × 19.05" × 7.56")
	Lifespan	Lamp 100,000 hours

▪ Typical Application



▪ Dimension (unit: mm)



## ▪ Accessory



DS-D42C08-H



DS-D42C04-H

## ▪ Available Model

- DS-D4218FI-CWF 600 × 337.5 mm/3<sup>rd</sup> Cabinet
- DS-D4218FI-CWF/A 3<sup>rd</sup> Cabinet Lamp Board

Distributed by



### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com