

## DS-K1T606 Series Face Recognition Terminal

DS-K1T606 series face recognition terminal adopts deep learning algorithm, which helps to recognize the face faster and more accurate. It also supports multiple authentication modes: face, card, fingerprint etc. Face recognition terminal helps managing the door opening/closing, which can apply to the scenarios of buildings, businesses, financial industries, and other important areas.



### Available Models

- DS-K1T606M
- DS-K1T606MF

### Features

- Wall mounting
- 5-inch LCD touch screen to display operation interface, etc.
- 2 MP wide-angle lens
- Wide dynamic range (WDR)
- Face recognition distance: 0.3 m to 1 m
- High performance processor with deep learning algorithm
- 3200 face capacity and 5000 fingerprint capacity
  - \* Only the device containing fingerprint module supports fingerprint related functions.
- Multiple authentication modes
- Accurate and fast face recognition function. The face recognition duration is no more than 1s per person and the face recognition accuracy rate is more than 99%
- Applies data to the device via TCP/IP or uploading data to the device via the USB flash drive
- Stand-alone operation
- Multiple languages supported: English, Thai, Spanish, and Arabic
- Supported attendance status: check in, check out, break out, break in, overtime in, and overtime out



- Transmits and saves the comparing results and the captured pictures to the client software or others
  - Device management, log search, and parameter settings via the device
  - Connects to one external card reader via RS-485 protocol
  - Connects to external access controller via RS-485 protocol and Wiegand protocol
  - Connects to secure door control unit to avoid the door opening when the terminal is destroyed
  - Voice prompts
  - Watchdog design for protecting the device and ensuring device running properly.
- \* **Biometric recognition products are not 100% applicable to anti-spoofing environments. If you require a higher security level, use multiple authentication modes.**

## Specification

Model	DS-K1T606M	DS-K1T606MF
Operation system	Linux	
LCD screen	5-inch LCD touch screen; resolution: 480 × 800	
Camera	2 MP; WDR; wide-angle lens	
1:N face recognition duration	≤ 1s/person	
Face recognition accuracy rate	≥ 99%	
Face recognition distance	0.3 m to 1 m	
Face capacity	3200	
Fingerprint capacity	/	5000
Card capacity	5000	
Event capacity	100,000	
Communication mode	10/100 Mbps self-adaptive network interface; Wi-Fi	
Interface	RS-485 × 1, Wiegand × 1, USB × 1, lock × 1, exit button × 1, tamper × 1, alarm input × 2, alarm output × 1, door contact × 1	
Power supply	12 VDC/2 A (centralized power supply)	
Working temperature	-20 °C to 50 °C (-4 °F to 122 °F)	
Working humidity	10% to 90% (no condensing)	
Installing method	Wall mounting (with/without gang box)	
Dimensions	281.5 mm × 113 mm × 45 mm (11.08" × 4.45" × 1.77")	
Application situation	Indoor; outdoor	
Protection Level	IP65	

\* *Exposing the equipment to direct sun light, low ventilation or heat source such as heater or radiator is forbidden (ignorance can cause fire danger).*

\* *For device with fingerprint module, we suggest that do not install the device outdoors.*

Distributed by

**HIKVISION****Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**

T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**

T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**

T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**

T +1-866-200-6890  
sales.canada@hikvision.com

**Hikvision Thailand**

T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**

T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**

T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**

T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**

T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**

T +601-7852-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**

T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**

Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**

T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**

T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**

T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**

T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**

T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**

T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**

T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**

T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**

T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**

T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**

T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**

T +82-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**

sales.colombia@hikvision.com