

AXIS T94C01L Recessed Mount

Discreet and elegant installation in drop ceilings

AXIS T94C01L Recessed Mount is an indoor mount for drop ceiling installations. It comes with a single-screw ceiling attachment for quick and easy installation. AXIS T94C01L Recessed Mount enables sleek, elegant and discreet recessed ceiling installations of Axis indoor cameras, compatible with AXIS M42 series and AXIS Companion Dome mini LE. It features a patent-pending single-screw ceiling attachment design, which makes the installation quick and easy without having to remove the ceiling tile. Axis fixed dome camera attached to the recessed mount is embedded into the ceiling, revealing only the camera dome and the low-profile cover ring.

- > [Quick and easy installation in drop ceilings](#)
- > [Elegant and discreet recessed ceiling installations](#)
- > [Compatible with AXIS M42 series as well as AXIS Companion Dome mini LE](#)



AXIS T94C01L Recessed Mount

General													
Supported products	AXIS M42-V/-LV Series AXIS Companion Dome mini LE												
Casing	Material: 54% recycled plastic Color: white NCS S 1002-B												
Sustainability	PVC free												
Mounting	Recessed in drop ceilings												
Environment	Indoor												
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)												
Approvals	Safety IEC/EN/UL 62368-1 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, IEC/EN 62262 IK08												
Dimensions	Outer dimensions Length: 252 mm (9.9 in), Height: 140 mm (5.5 in)												
	<table border="1"> <tbody> <tr> <td>Weight</td> <td>260 g (0.57 lb)</td> </tr> <tr> <td>Maximum load</td> <td>600 g (1.32 lb)</td> </tr> <tr> <td>Cable routing</td> <td>Top: cable hole</td> </tr> <tr> <td>Included accessories</td> <td>Installation guide, gasket</td> </tr> <tr> <td>Optional accessories</td> <td>AXIS Safety Wire 3 m</td> </tr> <tr> <td>Warranty</td> <td>3-year warranty, see axis.com/warranty</td> </tr> </tbody> </table>	Weight	260 g (0.57 lb)	Maximum load	600 g (1.32 lb)	Cable routing	Top: cable hole	Included accessories	Installation guide, gasket	Optional accessories	AXIS Safety Wire 3 m	Warranty	3-year warranty, see axis.com/warranty
Weight	260 g (0.57 lb)												
Maximum load	600 g (1.32 lb)												
Cable routing	Top: cable hole												
Included accessories	Installation guide, gasket												
Optional accessories	AXIS Safety Wire 3 m												
Warranty	3-year warranty, see axis.com/warranty												
	Environmental responsibility: axis.com/environmental-responsibility												